

Dimensiones (mm) y Peso (Kg/m) en Caños de Acero Inoxidable (Stainless Steel Pipes Chart)

NPS	Actual OD	5s	5	10s	10	20	30	STD 40s	40	60	XS 80s	80	100	120	140	160	XXS
1/8	0,405 10,30							1,73 0,37			2,41 0,47						
1/4	0,540 13,70							2,24 0,64			3,02 0,82						
3/8	0,675 17,10							2,31 0,87			3,20 1,12						
1/2	0,840 21,30	1,65 0,81	1,65 0,81	2,11 1,02	2,11 1,02			2,77 1,29			3,73 1,64					4,75 1,97	7,47 2,59
3/4	1,050 26,70	1,65 1,03	1,65 1,03	2,11 1,30	2,11 1,30			2,87 1,71			3,91 2,23					5,54 2,93	7,82 3,69
1	1,315 33,40	1,65 1,31	1,65 1,31	2,77 2,13	2,77 2,13			3,38 2,54			4,55 3,29					6,35 4,30	9,09 5,53
1.1/4	1,660 42,20	1,65 1,67	1,65 1,67	2,77 2,73	2,77 2,73			3,56 3,44			4,85 4,53					6,35 5,69	9,70 7,88
1.1/2	1,900 48,30	1,65 1,93	1,65 1,93	2,77 3,16	2,77 3,16			3,68 4,11			5,08 5,49					7,14 7,35	10,16 9,69
2	2,375 60,30	1,65 2,42	1,65 2,42	2,77 3,99	2,77 3,99			3,91 5,52			5,54 7,60					8,71 11,26	11,07 13,65
2.1/2	2,875 73,00	2,11 3,75	2,11 3,75	3,05 5,34	3,05 5,34			5,16 8,77			7,01 11,59					9,53 15,15	14,02 20,72
3	3,500 88,90	2,11 4,59	2,11 4,59	3,05 6,56	3,05 6,56			5,49 11,47			7,62 15,51					11,13 21,67	15,24 28,11
3.1/2	4,000 101,60	2,11 5,25	2,11 5,25	3,05 7,53	3,05 7,53			5,74 13,78			8,08 18,92						16,15 34,56
4	4,500 114,30	2,11 5,93	2,11 5,93	3,05 8,50	3,05 8,50			6,02 16,32			8,56 22,66			11,13 28,75		13,49 34,05	17,12 41,66
5	5,563 141,30	2,77 9,61	2,77 9,61	3,40 11,74	3,40 11,74			6,55 22,10			9,53 31,44			12,70 40,90		15,88 49,87	19,05 58,31
6	6,625 168,30	2,77 11,47	2,77 11,47	3,40 14,04	3,40 14,04			7,11 28,69			10,97 43,21			14,27 55,03		18,24 68,53	21,95 80,43
8	8,625 219,10	2,77 15,00	2,77 15,00	3,76 20,27	3,76 20,27			8,18 43,20		10,81 53,90	12,70 65,63		15,06 76,93	18,24 91,73	20,62 102,47	23,01 112,97	22,23 109,57
10	10,750 273,10	3,40 22,95	3,40 22,95	4,19 28,20	4,19 28,20			9,27 61,22		12,70 82,80	12,70 82,80	15,06 97,27	18,24 116,38	21,41 134,90	25,40 157,51	28,58 174,95	25,40 157,51
12	12,750 323,90	3,96 31,72	4,19 33,60	4,57 36,54	4,57 36,54	6,35 50,48	8,38 66,20	9,53 75,01	10,31 80,94	14,27 110,62	12,70 98,95	17,45 133,88	21,41 162,14	25,40 189,82	28,58 211,31	33,32 242,40	25,40 189,82
14	14,000 355,60	3,96 34,86		4,78 41,99	6,35 55,53	7,92 68,95	9,53 82,58	9,53 82,58	11,13 96,00	15,06 128,42	12,70 109,04	19,05 160,54	23,80 197,74	27,76 227,88	31,75 257,47	35,71 286,04	
16	16,000 406,40	4,19 42,20		4,78 48,07	6,35 63,61	7,92 79,03	9,53 94,70	9,53 94,70	12,70 125,20	16,66 162,59	12,70 125,20	21,41 206,40	26,19 249,34	30,94 290,88	36,53 338,32	40,46 370,74	
18	18,000 457,20	4,19 47,46		4,78 54,15	6,35 71,69	9,53 89,10	12,70 124,32	9,53 106,83	14,27 158,27	19,05 209,00	12,70 141,35	23,80 258,29	29,36 314,54	34,93 369,34	39,67 414,75	45,24 466,67	
20	20,000 508,00	4,78 60,23		5,54 69,70	6,35 79,76	9,53 118,93	12,70 157,51	9,53 118,93	15,06 185,89	20,62 251,65	12,70 157,51	26,19 315,97	32,54 387,41	38,10 448,30	44,45 515,94	49,99 573,31	
24	24,000 609,60	5,54 83,80		6,35 95,92	6,35 95,92	9,53 143,20	14,27 212,72	9,53 143,20	17,45 258,74	24,59 360,21	12,70 189,92	30,94 448,30	38,89 555,76	46,02 649,44	52,37 730,72	59,51 819,70	
30	30,000 762,00	6,35 120,15		7,92 149,55	7,92 149,55	12,70 238,28	15,88 296,68	9,53 179,56			12,70 238,28						
32	32,000 812,80				7,92 159,62	12,70 254,44	15,88 316,88	9,53 191,69	17,48 348,11		12,70 254,44						
34	34,000 863,60				7,92 169,64	12,70 270,50	15,88 336,96	9,53 203,74	17,48 370,22		12,70 270,50						
36	36,000 914,40				7,92 286,75	12,70 357,28	15,88 215,93	9,53 215,93	19,05 427,09		12,70 286,75						

Ref.. Valores en Negro: Espesor de pared en mm - Valores en Rojo: Peso en Kg/m